

**DYNATRAC**  
TIRES

**MEDIUM TRUCK TIRES**



**DYNATRAC**  
TIRES

## BUFFING GUIDELINES

**DYNATRAC**  
TIRES

Tire Size	Tread Design	Buff Radius		Max Buff Width	
		IN	MM	IN	MM
8R19.5	RA200	19.6	500	6.1	156
10R17.5	RA200	29.9	760	8.1	206
10R22.5	DT340	30.7	780	8.0	203
11R22.5	RL280+	29.1	740	8.6	220
11R22.5	RF110+	35.4	900	8.9	218
11R22.5	DL380	35.8	910	8.8	224
11R22.5	DT340	30.7	780	8.4	213
11R22.5	RA200	28.7	730	8.5	216
11R22.5	RD240	30.7	780	8.4	215
11R24.5	RL280+	29.1	740	8.7	220
11R24.5	RF110+	31.1	790	8.3	213
11R24.5	DL380	35.8	910	8.8	224
11R24.5	DT340	30.7	780	8.3	213
11R24.5	RA200	28.7	730	8.5	216
11R24.5	RD240	30.7	780	8.4	215
215/75R17.5	RA200	22.8	580	6.9	176
225/70R19.5	DT340	24.0	610	7.0	180
225/70R19.5	RA200	25.5	650	7.0	180

Tire Size	Tread Design	Buff Radius		Max Buff Width	
		IN	MM	IN	MM
235/75R17.5	RA200	26.3	670	7.4	190
245/70R19.5	DT340	24.8	630	7.8	200
245/70R19.5	RA200	24.4	620	7.9	202
255/70R22.5	DT320	24.8	630	7.8	200
255/70R22.5	MA400	31.8	810	7.9	202
255/70R22.5	RA200	31.8	810	8.1	206
265/70R19.5	RA200	31.8	810	8.2	210
275/70R22.5	RA200	33.4	850	8.6	220
285/75R24.5	RL280+	35.2	895	9.0	229
285/75R24.5	RF110+	31.4	800	8.6	220
285/75R24.5	DL380	36.2	920	9.1	232
285/75R24.5	RA200	35.8	910	8.8	224
295/75R22.5	RL280+	36.6	930	9.3	237
295/75R22.5	RF110+	35.4	900	9.0	229
295/75R22.5	DL380	37.7	960	9.4	240
295/75R22.5	DT340	39.3	1000	9.2	235
295/75R22.5	RA200	37.7	960	9.0	231
385/65R22.5	MA440	33.4	850	12.0	306

# *DYNATRAC*

## *TIRES*

### **Dynatrac Tires**

**1995 Tiffin Ave, Suite 205  
Findlay, Ohio 45840 U.S.A.  
Tel: 844.432.9729**

STOCK #88415 (3/18)

[www.herculestirecommercial.com](http://www.herculestirecommercial.com)